

E5R4052A

5MP Day & Night Fixed IR Dome IP Camera


www.meritlilin.com




Resolution



FCC



Day & Night



WDR



Waterproof



Mobile App

- High quality imaging with progressive scan CMOS
- Up to 30M IR distance
- Fixed lens
- 3D DNR
- Built-in micro SD card slot
- Built-in microphone
- DC12V/PoE power supply
- IP66
- Support mobile surveillance by smart phones

Diagram

Video Performance	
Minimum Illumination	Color 0.002Lux @(F1.2,AGC ON) ; B/W 0 lux @ IR ON
Lens / Night Vision (Infrared LED)	
Focal Length	3.6mm
Iris / Aperture	F1.6
Iris Control	Fixed
Angle of View (H)	79°
Angle of View (V)	56°
Angle of View (D)	106°
Peak Wavelength	850nm
Radiant Distance	30M
Sensor	
Pick Up Element	1/2.7" CMOS image sensor
Effective Pixels	2608(H) X 1960(V) = 5,111,680 (Pixels)
Certifications	
CE	Yes
FCC	Yes
IP Rating	IP66
PC Requirements	
CPU	Intel Core i7 or higher grade
OS	Windows 7 or above
RAM	8GB or more, Dedicated Graphics Card
Web Browser	Microsoft® Internet Explorer® 10 and later
Input / Output	
Microphone	Built-in Microphone
Audio	One-way Audio, G.711 u-law
Video Streaming	
Video Compression	H.265/HEVC Main Profile, H.264 Main Profile, Motion JPEG
Video Streaming	RTSP/UDP, RSTP/TCP, configurable streams in H.265 and H.264 and Motion JPEG, configurable frame rate and bandwidth
Number of Streams	3
Video Bitrate	128Kbps - 8192Kbps, Frame rate and bit rate controllable on-the-fly, VBR / CBR / GOP supported, H.264/H.265
Maximum Frame Rate	2592x1920 / 20 fps
Network Security	
Encryption	Base64 HTTP encryption, DDNS via HTTPS, AES-256 encryption
Authentication	Digest HTTP authentication, RTSP Authentication, TLS, DDNS via HTTPS
Access	Multiple user access levels with password protection
User accounts	7 user accounts available
Video Resolutions (H x V)	
Mainstream Resolution	2592x1920, 2304x1728, 2304x1280, 1920x1080, 1280x960, 1280x720
Substream Resolution	1280x720, 720x576, 720x480, 720x384, 640x480
Mobilestream Resolution	720x480,720x384, 640x480, 352x256
Video Functions	
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Schedule / Day (Color) / Night (Mono)
White Balance	Auto / Manual (Adjustable)
Electrical Shutter	1/30(1/25)s - 1/20000s
Sense Up	Off / x2 / x4
Auto Gain Control	6 / 12 / 18 / 24 / 30 / 36 dB
S/N Ratio	More than 48dB (AGC off)
3D Noise Reduction	Yes
Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip
EV (Exposure Value)	Adjustable

Integration	
Mobile Application	Integrated to LILIN mobile app (LILIN Pro), iPhone, iPad, Android support
Video Management	ONVIF Profile S / LILIN Navigator Enterprise 2.0 support, Third party VMS through LILIN HTTP API
SD Card Recording	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
Maintenance	Firmware update via HTTP and IP Scan Firmware available at web site
Event Triggers	Motion / Network lost detection / Global Counter / Virtual Input / Metadata
Event actions	FTP / SMTP / HTTP post / SD card / SAMBA / Global Counter / Virtual Input / Push Service notification
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network	
Ethernet	10Base-T / 100Base-TX, RJ-45
OSD	Text overlay for date, time, and camera name (position configurable text overlay for date, time, camera name)
CPU, Memory	Embedded SoC ARM Cortex-A7, 800MHz, 128MB DDR3, 64MB flash memory
OS	Embedded Linux 3.10
Network Protocols	IPv4, TCP, UDP, HTTP, HTTPS, SMTP, NTP, DDNS, FTP, ARP, DHCP, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S, SSL/TLS
Max number of online users	7 simultaneous users
Video Display	ActiveX
Log	System / Config / User / Record / Storage / Network
Power and Environment	
Starting Temperature	-10°C - +50°C (14°F - 122°F)
Operating Temperature	-30°C - +50°C (-22°F - 122°F)
Storage Temperature	-25°C - +60°C (-13°F - 140°F)
Humidity	0% ~ 95% RH
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 4W / PoE, 5.5W
Mechanical	
Dimension	Ø100 x 90(H) mm
Weight	438g
Casing Material	Aluminum alloy